Mega Five Trading Company Limited **27**" Indoor high-resolution LED Displays



The panel is made with the international golden ratio (16:9). It is perfect for showing videos, PowerPoint slides, and other content. Each LED Panel has a 27" diagonal in a 16:9 aspect ratio which allows most common formats in full without compression.

Quick installation and dismantle

Thanks to the cable-free connection design, it creates flexibility in installation and dismantles.

Save cost in installation

Not only cable-free features, thanks to the Ultra-thin and Ultra-light design, but the panel is also just 38mm thin and 5kg weight. It does not only save time on installation but also reducing the labor in installation and material on the wall mount.

Quick maintenance

Each panel contains 8 LED modules that can easily be replaced by using a magnetic tool at front of the wall. It can largely reduce the downtime of the wall.

Redundancy Power and Signal supply (Optional)

To offer the shortest downtime of the LED, the customer can select the optional redundancy power and signal supply module. This feature is highly recommended for the application in transportation, broadcasting, security and control room.





Adopt International golden ratio 16:9 Prefect splicing combination, Create multi-application suitable for all application

2K / 4K

(High: mm)

2,700.0 8x8 (216" 2,362.5 2,025.0 1,687.5 5x5 (136") 1,350.0 4x4 (108") 1,012.5 3x3 (82" 675.0 2x2 (54" 337.5 600 1200 4200 4800 1800 2400 3000 3600

(Width: mm)

		1x1	2x2	3x3	4x4	5x5	6x6	7x7	8x8
0).93	640 x 360	1280 x 720	1920 x 1080	2560 x 1440	3200 x 1800	3840 x 2160	4480 x 2520	5120 x 2880
1	25	480 x 720	960 x 540	1440 x 810	1920 x 1080	2400 x 1350	2880 x 1620	3360 x 1620	3840 x 2160
1	.56	384 x 216	768 x 432	1152 x 648	1536 X 864	1920 x 1080	2304 x 1296	2688 x 1512	3072 x 1728
1	l.87	320 x 180	640 x 360	960 x 540	1280 X 720	1600 x 900	1920 x 1080	2240 x 1260	2560 x 1440
	2.3	256 x 144	512 x 288	768 x 432	1024 X 576	1280 x 720	1536 x 864	1792 x 1008	2048 x 1152

Parameters

ltem	P0.93	P1.25	P1.56	P1.87	P2.3			
Pixel Pitch: mm	0.9375	1.25	1.56	1.87	2.3			
Pixel density: pix/m ²	113777	640000	409600	284444	182044			
Brightness: cd/m ²	500 600							
Scan:	Constrant current drive							
Work environment	Indoor							
Operating temperature	-30 °C ~ 60 °C							
Viewing Angle	H: 160° V:160°							
Module size: mm	160 x 168.75							
Cabinet resolution	640 x 360	480 x 270	384 x 216	320 x 180	256 x 144			
Cabinet size	600 x 337.5							
Thickness Cabinet: mm	38							
Cabinet material	Die Cast Aluminium							
Waterproof level	IP34							
Average power: w/m ²	180 225							
Refresh rate: HZ	<u>≤</u> 3840							
Net weight (per cabinet): kg	5							

*Parameters are subject to change from factory without notice in advance

16:9

Cabinet Dimension



Fit for all indoor applications

The LED panel not only supports traditional LED wall installation but also the wall with a curve design. It is widely used in Shopping mall, Television Studio, corporate meeting room, logo wall, and even cave application.

Shopping Mall



Meeting room



Corporation show room/wall

Television Broadcasting

Television Studio



Cave



Control Centre

Command Centre



